

INSTRUCTION FOR USE

RODO LIMITED

LUMB LANE DROYLSDEN GREATER MANCHESTER M437BU

UNITED KINGDOM

Glove reference : 84301-54312

Available sizes : 7/S 8/M 9/L 10/XL 11/XXL

Glove description :

13G black polyester with black PU palm

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work gloves ». Dexterity : 5

Moreover, this glove has been designed for the following applications :

Application :
Mechanical hazard - EN 388



4 1 3 1 X
Levels of performance

Abrasion resistance	4	(on 4 max)
Blade cut resistance	1	(on 5 max)
Tear resistance	3	(on 4 max)
Puncture resistance	1	(on 4 max)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

« X » means that the test hasn't been performed ; no protection is required

Protection limit :

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.