



## ■ TEGERA® 585

[Learn more](#)

Heat-resistant glove, fully lined, 1,3-1,5 mm split cowhide of top quality, aluminium, cut resistance level 3, KEVLAR® fiber, Cat. III, withstands contact heat up to 250°C, water and oil repellent palm, for allround work

## CHARACTERISTICS

- Highest level of protection
- Good fingertip sensitivity
- Good fit
- Flexible

## FUNCTIONS

- Cut resistant according to 388:2003 level 3
- Withstands contact heat up to 250°C
- Water and oil repellent palm
- Heat-resistant

**PREVENTS RISK OF**

burn injuries, heat injuries, cut injuries

**PRIMARY ENVIRONMENTS OF USE**

cut risk environments, warm surfaces, warm environments, moist environments, oily and greasy environments, dirty environments, harsh environments

**PRIMARY AREAS OF USE**

engineering, metalwork, hot work, mining

**PRIMARY INDUSTRIES OF USE**

mining, oil, gas, petrochemical, metal fabrication, automotive

**TYPE OF WORK**

Heavy weight

**SPECIFICATION**

TYPE Heat protection gloves

CATEGORY Cat. III

PALM MATERIAL Split cowhide of top quality

BACK MATERIAL Aluminium

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

LENGTH 375-415 mm

COLOUR Grey, Red

PAIRS PER: BUNDLE/CARTON 3/30

DISPLAY TYPE Thread

FASTENING Hook-and-loop

CUFF STYLE Extended safety cuff

CUT RESISTANCE Cut resistance level 3


INNER MATERIAL SPECIFICATION Para-aramid, Cotton

OUTER MATERIAL SPECIFICATION Leather

**COMPLIANCE**



TP TC 019:2011



EN 12477:2001+A1:2005



EN 420:2003 +A1:2009

EN 1149-2:1997 R:41.8\*10<sup>6</sup>Ω

Type A

**FEATURES**



SIZE	ARTICLE NUMBER	EAN
8	585-8	7340118305271
9	585-9	7340118305295
10	585-10	7340118305219
11	585-11	7340118305233
12	585-12	7340118305257

**ejendals**

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | [info@ejendals.com](mailto:info@ejendals.com) | [order@ejendals.com](mailto:order@ejendals.com)