



HAND PROTECTION RANGE

# TECHNICAL PRODUCT DATASHEET

GENERAL HANDLING

UPDATED: 16/09/2019

## PCP-Carbon

Anti-static PU palm coated PU/carbon shell.

Machine knitted seamless construction of PU and carbon filament liner providing anti-static properties. Tough polyurethane coating on the front face and over finger tips. Excellent dexterity and grip combined with improved mechanical protection.



### FEATURES AND TECHNOLOGY



### TYPICAL INDUSTRIES



### TECHNICAL INFORMATION

ORDER REF #	G/PCP-CARBON
COATING MATERIAL	PU
PACKING	PER PACK: 10    PER CASE: 120
SIZES AVAILABLE	7 (S), 8 (M), 9 (L), 10 (XL)
EU TYPE CERTIFICATION BY	Bureau Veritas, Wilhelm-Hennemann-Straße 8, 19061 Schwerin, Germany (Notified Body No. 2004)

### CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)



<sup>1</sup> 'X' denotes not tested.  
<sup>2</sup> Where applicable, EN388:2016 scores take precedent and are ongoing.  
<sup>3</sup> There is no correlation between couple test levels and EN ISO 13997 /TDM cut test levels.



HAND PROTECTION RANGE

# TECHNICAL PRODUCT DATASHEET

GENERAL HANDLING

UPDATED: 16/09/2019

### CERTIFICATION LEGENDS

<b>EN388:2016</b>	<b>EN388:2016 Blade Cut TDM EN ISO 13997*</b>	<b>NEWTON LEVEL</b>	<b>EN407:2004</b>	<b>EN511:2006</b>
Abraction (0-4)	EN ISO 13997	≥ 30 F	Burning Behaviour (0-4)	Consecutive Cold (0-4)
Cut (0-5)	NEWTON	≥ 22 E	Contact Heat (0-4)	Contact Cold (0-4)
Tear (0-4)		≥ 15 D	Convective Heat (0-4)	Water Penetration (0-5)
Puncture (0-4)		≥ 10 C	Radiant Heat (0-4)	
TDM Cut (A-F)		≥ 5 B	Small Splashes Molten Metal (0-4)	
Impact (0-5)		> 2 A	Large Quantity Molten Metal (0-4)	

\* For dulling during cut resistance test (6.2), the couple test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

<sup>1</sup> Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm<sup>2</sup> where the cuff is tested also tested. <sup>2</sup> 'X' denotes Not Tested. <sup>3</sup> Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between couple test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.

### FURTHER INFORMATION

**STORAGE / TRANSPORT:** Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

**PRECAUTIONS BEFORE USE:** 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

**CONSTITUENTS / ALLERGIES:** Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit: <https://www.ultimateindustrial.co.uk/product/1129-PCP-Carbon>

If appropriate to the product, CE/UK Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address or by contacting UCI customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks™ or registered trademarks of their respective holders. © UCI Limited, 2019.



Phone: +44 (0)1902 451 451  
Fax: +44 (0)1902 451 271  
Email: sales@ultimateindustrial.co.uk  
Web: www.ultimateindustrial.co.uk



© 2019, Ultimate Cleaners (Industrial) Ltd.  
Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK.  
Registered in England No. 2035621



Phone: +44 (0)1902 451 451  
Fax: +44 (0)1902 451 271  
Email: sales@ultimateindustrial.co.uk  
Web: www.ultimateindustrial.co.uk



© 2019, Ultimate Cleaners (Industrial) Ltd.  
Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK.  
Registered in England No. 2035621