

Information User instruction

Safety gloves against chemical and mechanical risks

Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG Elso-Klöver-Str. 6, 21337 Lüneburg Postfach 24 47 · 21314 Lüneburg GERMANY

Type uvex rubiflex S - NB27B

Basic glove material cotton interlock

Available sizes 7, 8, 9, 10, 11

Tel.: +49 4131 9502-0 Fax: +49 4131 84338 Email: gloves@uvex.de Website: uvex-safety.de

Coating material Special NBR (nitrile butadiene

rubber)

Smallest packing unit 80 Pairs

Pictogram and performance levels

EN 374: 2003



JKL Performance level

n-heptane Class 5 (> 240 min) Sodium hydroxide 40% Class 6 (> 480 min) Sulphuric acid 96% Class 2 (> 30 min)

Pictogram and performance levels according to EN 374:2003 (lowest performance level: 1/highest performance: 6)


The sampling for penetration testing is made by general inspection level according to DIN 2859, part 1 with AQL 4.0.

Please note: The actual period of protection on the job is affected by many factors (temperature, abrasion, etc.) and can therefore differ from the performance level!

EN 388: 2003







Pictogram and performance levels according to EN 388:2003 (highest performance level: 4/cut resistance: 5)

All levels only apply to the coated areas of the glove.

EC notified body Centexbel Gent

Technologiepark 7 · BE - 9052 Zwijnaarde (Gent), Belgium

No.: 0493

Cleaning Cleaning only possible when not working with aggressive chemicals. Carefully rinse gloves under

lukewarm running water.

Storage Store in a dark, dry place.

Handling Thoroughly check before use for damage. Defective gloves should not be used. All technical data refers

to the state of the gloves at delivery, unused, not stretched and at ambient temperature (EN 374).

Gloves must be disposed of when the permeation time expires.

After contamination, a change of performance cannot be excluded.

We are not aware of any substances in this product that could cause an allergic reaction.

Disposal The gloves should be disposed of properly as household waste. If they come into contact with chemicals,

please consult the chemical manufacturer's waste disposal guidelines.

Warning Gloves should not be worn where there is a risk of being caught in moving machinery parts.

protecting people