

Seamless Nylon PVC Dot - Fingerless

30121-4

30221-4

S, M, L, XL 2XL





Notified Body: Bureau Veritas

CAREFULLY READ INSTRUCTIONS BEFORE USE

This product is designed to provide protection against: Mechanical Risks. No item of PPE can provide full protection - care must always be taken whilst carrying out the activity.

EN 420:2003+A1:2009 Protective Gloves – General Requirements

Fitting & Sizing: Only wear products of a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimum level of protection.

Storage & Transport: Store the product in a well ventilated area away from extremes of temperature & strong odours.

Inspection Before & After Use: Discard and replace damage products before use. If in doubt consult manufacturer.

Cleaning: It is recommended that this product should not be washed or dry-cleaned.

EN 388:2003 Protective Gloves Against Mechanical Risks

Test	Level Achieved	Maximum Level
Abrasion Resistance	4	(4)
Blade Cut Resistance	1	(5)
Tear Resistance	4	(4)
Puncture Resistance	1	(4)

Note: Performance levels apply to the palm area of the hand.

Warning: These gloves will not prevent crushing injuries, or injuries associated with vibration. They are not to be worn when there is a risk of entanglement by moving parts of machinery.

Gloves containing natural rubber latex might contain ingredients which are known to be a possible cause of allergies in sensitised persons. If any allergic reaction should occur then medical advice should be obtained immediately.

EN 388:2003

To find DOC documentation search for your desired product at- www.supertouch.com