



**TraffiGlove**  
THE HAND PROTECTION SPECIALISTS



**PROTECTIVE GLOVES AGAINST MECHANICAL RISK FOR GENERAL USE**

**USER INFORMATION**

The information contained herein is intended to assist the wearer in the selection of personal protective equipment. The result of the laboratory tests should help with correct glove selection, however it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the glove suitability for the intended use.

**Warning** - Gloves not to be worn when there is risk of entanglement by moving parts of a machine.

**CE MARK**

This type of glove has been subject to an EC type examination by a notified body (see below) according to European standards. The CE mark printed on the gloves signifies that they meet the requirements of European Directive No. 89/686 EEC regarding Personal Protective Equipment.

**CERTIFIED BY**

SGS United Kingdom Limited, No 0120  
Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA  
Tel: +44 (0) 1934 522 917 Fax: +44 (0) 1934 522 137

**CLEANING AND MAINTENANCE**

Both new and used gloves should be inspected to ensure no damage is present prior to use. Gloves should not be left in contaminated condition if re-use is intended, in which case gloves should be cleaned as far as possible with suitable damp cloth, provided no serious hazards exists, before removal from the hands. Excess contaminant should first be removed. When the contaminant is not removable or presents a potential hazard it is advisable to ease left and right hand gloves off alternatively using the gloved hand so that the gloves are removed without the contaminant contacting the bare hands.

**SIZE GUIDE**

The fit dimensions of this glove falls outside the standard length parameters of EN 420:2003. The glove is designed to minimise entanglement risks at the cuff whilst maintaining a dexterous, tactile fit. The end user should fully assess the suitability of the glove to the task prior to first use.

06 - XSmall    07 - Small    08 - Medium  
09 - Large    10 - Xlarge    11 - 2Xlarge

**PACKING AND STORAGE**

The gloves are packed in bundles, along with this leaflet. The bundled gloves are then placed in cardboard cartons. This is suitable for transportation and storage. Store the gloves in a cool dry place and out of direct sunlight

**OBSCOLESCENCE**

Stored correctly, the gloves physical properties will not change for up to five years.

**DISPOSAL**

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.

**ALLERGIC REACTIONS**

These gloves may contain Natural Rubber Latex (NRL) and may cause allergic reactions. In the case of an allergic reaction, please discontinue use immediately and seek medical advice. A list of substances is available on request.

**EN 388:2003 - MECHANICAL RISKS**

Protection against mechanical hazards is expressed by a pictogram followed by four numbers (performance levels), each representing test performance against a specific hazard. Levels are only assured on the palm of the glove.



A - Abrasion Resistance (0-4)  
B - Blade / Cut Resistance (0-5)  
C - Tear Resistance (0-4)  
D - Puncture Resistance (0-4)

**EN 407:2004 - THERMAL RISKS (HEAT OR FIRE)**

The nature and degree of protection is shown by a pictogram followed by a series of six performance levels, relating to specific protective qualities. The higher the number, the better the test result. The following is tested:



A - Resistance to burning behaviour (0-4)  
B - Contact heat resistance (0-4)  
C - Convective heat resistance (0-4)  
D - Radiant heat resistance (0-4)  
E - Resistance to small splashes of molten metal (0-4)  
F - Resistance to large quantities of molten metal (0-4)

**ASTM F265**

The glove has been through several rigorous tests, rated as Hazard Risk Category 2 (NFPA 70E) having achieved an Arc Thermal Protective Value (ATPV) of 8.6 cal/cm<sup>2</sup> for arc flash.

# Traffi GLOVE

**TG5180 - Size 06**

Product Code **www.traffiglove.com** Glove Size

EN 388 Marking

EN 407 Marking

CE Marking

ANSI Cut Level

Intermediate Design

Arc Rating

ATPV = 8.6Cal/cm<sup>2</sup>  
Arc Category level 2