

USER INSTRUCTION BOOKLET

www.traffiglove.com



The user information contained in this document applies to every glove in our range

AFFIX PACK BARCODE LABEL HERE

SAFETY IN COLOURS

Here is the innovative, proven, easy to use 3 colour system designed to give your team added protection and you extra peace of mind. At a glance you and your team will know what a particular glove is for, and if they have the right degree of protection.



RED CUT LEVEL 1 2
WARNING LOWER CUT PROTECTION

Our **RED** gloves are ideal for tasks that involve a low cut risk, such as general product handling, warehouse and assembly line work and some low risk construction jobs. These Cut Level 1 gloves provide adequate protection for a wide range of tasks while the RED colour serves as a warning, reminding the wearer to consider whether further protection is required when switching to a different task.



AMBER CUT LEVEL 3 4
BE AWARE MEDIUM CUT PROTECTION

Our **AMBER** gloves offer a medium level of cut protection, which makes them the ideal choice for second fix construction trades, mechanical and electrical trades, steel fixing and handling materials with sharp edges. The AMBER gloves are finished with a variety of coatings to give you plenty of choice within the range.



GREEN CUT LEVEL 5
SAFE TO GO HIGHER CUT PROTECTION

Our **GREEN** gloves provide the highest level of cut protection, so they are the best choice for higher cut risk tasks such as applying cladding, swarf and metal work and handling glass or sheet metal with cut edges. They also provide the higher protection necessary when dealing with unknown risks, for example, in the waste and recycling industries.

EN 388 Compliance

The TraffiGlove colour coded system relates to the gloves performance on the EN 388 test for cut resistance.

For further information and latest product news please visit us at: www.traffiglove.com

Abrasion Resistance (Cycles)
Blade Cut Resistance (Index)
Tear Resistance (Newtons)
Puncture Resistance (Newtons)

	Performance Level				
	1	2	3	4	5
Abrasion Resistance (Cycles)	100	500	2000	8000	N/A
Blade Cut Resistance (Index)	1.2	2.5	5.0	10.0	20.0
Tear Resistance (Newtons)	10	25	50	75	N/A
Puncture Resistance (Newtons)	20	60	100	150	N/A



The Original
COLOUR CODED SAFETY GLOVES
Invented by TraffiGlove



PROTECTIVE GLOVES AGAINST MECHANICAL RISK FOR GENERAL USE

USER INFORMATION

This product has been made to protect against risks as expressed by the pictograms below. These pictograms show where to find the information relating to them on the glove to determine the performance level covered against the specific hazard. Users must be aware that actual conditions of use cannot be simulated and it is the responsibility of the user, not the manufacturer to determine the glove suitability for the intended use.

CE MARK

This type of glove has been subject to an EC type examination by a notified body (see below) according to European standards. The CE mark printed on the gloves signifies that they meet the requirements of European Directive No. 89/686 EEC regarding Personal Protective Equipment.

CERTIFIED BY

Intertek Testing Services, Centre Court, No 0362 Meridian Business Park, Meridian N, Leicester, LE19 1WD
Tel: +44 (0) 116 263 0330 Fax: +44 (0) 116 263 0311

MAINTENANCE

Both new and used gloves should be inspected to ensure no damage is present prior to use. No specific cleaning or maintenance is advocated as the performance after laundering is unknown.

SIZE GUIDE

The fit dimensions of this glove falls outside the standard length parameters of EN 420:2003. The glove is designed to minimise entanglement risks at the cuff whilst maintaining a dexterous, tactile fit. The end user should fully assess the suitability of the glove to the task prior to first use.

06 - XSmall 07 - Small 08 - Medium
09 - Large 10 - Xlarge 11 - 2Xlarge

STORAGE

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

OBsolescence

This product should not deteriorate if stored as recommended (see above) Service life cannot be specified and depends on application and responsibility of user to ascertain suitability of the glove for its intended use.

EN 388 - MECHANICAL RISKS

Protection against mechanical hazards is expressed by a pictogram followed by four numbers (performance levels), each representing test performance against a specific hazard. Levels are only assured on the palm of the glove.



EN 388

A B C D

A - Abrasion Resistance (0-4)
B - Blade / Cut Resistance (0-5)
C - Tear Resistance (0-4)
D - Puncture Resistance (0-4)



EN 511

A B C

A - Convective Cold (0-4)
B - Contact Cold (0-4)
C - Water Permeation 30mins (0-1)



EN 407

A B C D E F

A - Resistance to burning behaviour (0-4)
B - Contact heat resistance (0-4)
C - Convective heat resistance (0-4)
D - Radiant heat resistance (0-4)
E - Resistance to small splashes of molten metal (0-4)
F - Resistance to large quantities of molten metal (0-4)

ALLERGIC REACTIONS

These gloves may contain Natural Rubber Latex (NRL) and may cause allergic reactions. In the case of an allergic reaction, please discontinue use immediately and seek medical advice. A list of substances is available on request.

DISPOSAL

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.

Traffi GLOVE

