



Technical Datasheet



Standards and Pictograms:

EN388:2016















Certification:



EC type examination carried out by: SATRA Quality Assurance Ltd, SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321)





Gloves should be stored in a cool, dry environment in the original packaging and $out\ of\ direct\ sunlight.\ Keep\ away\ from\ sources\ of\ ozone\ or\ ignition.$

Hantex® NGX-R



NGX-R™

Lightweight and seamless knitted red polyester liner with a tough black nitrile coating for excellent dexterity and abrasion resistance. Close fitting, knit wrist style. Nitrile palm coating gives excellent grip in dry applications and resistance to oils and grease.

Also available in a black liner version with black nitrile palm coating (NGX-BK).

ADDED FEATURES



Individual Retail Polybag



Multilingual UI

Typical Applications:



Detailed Assembly ► Construction ► Automotive Inspection Light Fabrication

Packing:



Per Case:

120 pairs



Per Pack:

10 pairs bulk polybag, 1 pair polybag

Available Sizes:



7-10

Maintenance:



Both new and old gloves should be thoroughly inspected before use to ensure no damage is present. Gloves should not be left in a contaminated condition if reuse is intended - if contaminated, gloves should be cleaned as far as possible.





Phone: +44 (0)1902 451 451



Email: sales@ultimateindustrial.co.uk



Web: hantexsafety.com | ultimateindustrial.co.uk









