

■ TEGERA® 629

[Learn more](#)

Cut resistant glove, latex, 3/4 dipped, granulated, cut resistance level C, 10 gg, Dyneema®, glass fibre thread, nylon, Cat. II, waterproof palm, for assembly work

CHARACTERISTICS

- Durable
- Light
- Good fingertip sensitivity
- Flexible
- Comfortable
- Good grip
- Good fit

FUNCTIONS

- Withstands contact heat up to 100°C
- Water repellent palm and knuckle



PREVENTS RISK OF

cut injuries, abrasion injuries, grazes, scratches, lacerations, contact with dirt, contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE

cut risk environments, wet environments, moist environments, dirty environments

PRIMARY AREAS OF USE

building and construction, installation work, tiling, concrete work, engineering, metalwork, glass industry work, forest work, agricultural work, repair work

PRIMARY INDUSTRIES OF USE

agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

LINING MATERIAL 10 gg, Dyneema®, Glass fibre thread, Nylon, Polyester

LENGTH 220-260 mm

GRIP DESIGN Crinkled grip pattern

COLOUR Black, Grey

PAIRS PER: BUNDLE/CARTON 12/120

DISPLAY TYPE Bag with euro slot

FASTENING Hook-and-loop

DIPPING 3/4 dipped

DIPPING MATERIAL Latex

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) TDM: 10.7 N


INNER MATERIAL SPECIFICATION UHMWPE (Ultra high molecular weight polyethylene), Nylon, Polyester, Glass fibre thread

OUTER MATERIAL SPECIFICATION Natural latex

COMPLIANCE



TP TC 019:2011




EN ISO 21420:2020



Contact heat rating valid for palm area only

FEATURES



SIZE	ARTICLE NUMBER	EAN
7	629-7	7392626064461
8	629-8	7392626064478
9	629-9	7392626064485
10	629-10	7392626064492
11	629-11	7392626064508

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com