# CUT RESISTANT GLOVES, HEAT PROTECTION GLOVES

LEGE



# **TEGERA**® INFINITY 8808



# SOFT, KNUCKLE DIPPED, CUT D GLOVE.

Dexterous cut resistant glove, level D, suitable for assembly work. Great fit thanks to 15 gg knitted with CRF<sup>®</sup> cut resistant technology. Knuckle dipped with super soft nitrile foam coated palm that provides good grip on greasy and oily surfaces. Reinforced thumb crotch for improved longevity. Protection against contact heat up to 100°C. Skin friendly with Derma-test and Oeko-Tex certificate.

## CHARACTERISTICS

- High level of protection
- Good fingertip sensitivity
- Good grip
- Extra comfortable
- Flexible
- Durable

## FUNCTIONS

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs
- Anatomically designed
- Oil and grease resistant
- Reinforcement between index finger and thumb



## PREVENTS RISK OF

cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with oil and fat

### PRIMARY ENVIRONMENTS OF USE

cut risk environments, moist environments, oily and greasy environments, dirty environments, harsh environments

### PRIMARY AREAS OF USE

fine assembly, assembly, machine operating, building and construction, carpentry, installation work, hvac installation, sheet-metal work, concrete work, engineering, transport work, machine driving, warehouse work, airport work, metalwork, glass industry work, repair work, paper industry work, service work, shop work

#### PRIMARY INDUSTRIES OF USE

pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

**TYPE OF WORK** 

## Medium weight SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves CATEGORY Cat. II **COLLECTION Infinity** LINING MATERIAL CRF<sup>®</sup> Technology, Glass fibre thread, Nylon, Spandex, 15 gg GRIP DESIGN Foam grip pattern COLOUR Black, Yellow PAIRS PER: BUNDLE/CARTON 6/120 DISPLAY TYPE Bulk pack DIPPING 3/4 dipped, Double-dipped DIPPING MATERIAL Nitrile, Nitrile foam, Waterbased PU CUFF STYLE Knitwrist cuff CUFF MATERIAL Textile CUT RESISTANCE (EN ISO 13997) Cut resistance level D CUT RESISTANCE (EN ISO 13997) TDM: 15 N INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Glass fibre thread, Elastane

OUTER MATERIAL SPECIFICATION Nitrile

# COMPLIANCE

EN 388:2016

4X43D



EN 420:2003 +A1:2009



TP TC 019:2011





li





**FEATURES** 



SIZE	ARTICLE NUMBER	EAN
6	8808-6	7340118384405
7	8808-7	7340118319834
8	8808-8	7340118319841
9	8808-9	7340118319858
10	8808-10	7340118319810
11	8808-11	7340118319827

Limavägen 28, SE-793 32 Leksand, Sweden Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice