



TEGERA® 882



[Learn more](#)

Synthetic glove, nitrile foam, fully dipped, micro foam grip pattern, 15 gg, nylon, Cat. II, withstands contact heat up to 100°C, water and oil repellent, for fine assembly work

CHARACTERISTICS

- Good fit
- Durable
- Good grip
- Good fingertip sensitivity
- Flexible

FUNCTIONS

- Withstands contact heat up to 100°C
- Water and oil repellent

PREVENTS RISK OF

abrasion injuries, scratches, lacerations, contact with dirt, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

oily and greasy environments, dirty environments

PRIMARY AREAS OF USE

fine assembly, assembly, inspection work, building and construction, carpentry, installation work, tiling, construction, soil preparation

PRIMARY INDUSTRIES OF USE

machinery and equipment, mro, building and construction, automotive, transportation, utilities

TYPE OF WORK

Light weight

SPECIFICATION

TYPE All-round work gloves, Heat protection gloves

CATEGORY Cat. II

LINING MATERIAL Nylon, 15gg

LENGTH 230-260 mm

GRIP DESIGN Micro foam grip pattern

COLOUR Black

PAIRS PER: BUNDLE/CARTON 12/60


DISPLAY TYPE Bag with euro slot

DIPPING Fully dipped



DIPPING MATERIAL Nitrile foam

INNER MATERIAL SPECIFICATION Nylon

OUTER MATERIAL SPECIFICATION Nitrile



EN ISO 21420:2020



! Contact heat rating valid for palm area only

SIZE	ARTICLE NUMBER	EAN
7	882-7	7392626040199
8	882-8	7392626040205
9	882-9	7392626040212
10	882-10	7392626040229
11	882-11	7392626040236

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com