

## PETRO VE780



PVC COATED COTTON LINED GLOVE OIL TYPE

Model VE780



### Product specifications

Chemical PVC. PVC on cotton knitted lining gauge 13. Rough-textured hand. Length: 30 cm. Thickness: 1.30 mm.

Support: cotton.  
Coating: PVC.  
Thickness: 1,30 mm.

#### COLOUR

Blue

#### SIZE

08, 09, 10

Product Features and Benefits



0%  
SILICONE  
LATEX



Textured structure

Good grip of handled objects

PVC

Good resistance to abrasion  
Material very resistant to oils, chemicals and  
petroleum derivatives

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements  
5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)  
4: Resistance to abrasion (from 1 to 4)  
1: Resistance to cutting (from 1 to 5)  
3: Resistance to tear (from 1 to 4)  
1: Resistance to puncture (1 to 4)  
X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 1: Terminology and performance requirements for chemical risks.

TYPE B: Type B - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 3 chemicals at level 2 according to EN16523-1: 2015 (from 1 to 6).  
.: Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.  
J 2 > 30 mn: n-Heptane (J) CAS 142-85-5  
K 6 > 480 mn: Sodium hydroxide 40% (K) CAS 1310-73-2  
L 4 > 120 mn: Sulphuric acid 96 % (L) CAS 7664-93-9



EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro-organisms risks.

BACTERIA + FUNGI : BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.



REGULATION 2016/425 PERSONAL PROTECTIVE EQUIPEMENT, AS AMENDED TO APPLY IN GB

EN420:2003+A1:2009 General requirements  
5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)  
4: Resistance to abrasion (from 1 to 4)  
1: Resistance to cutting (from 1 to 5)  
3: Resistance to tear (from 1 to 4)  
1: Resistance to puncture (1 to 4)  
X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)





EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 1: Terminology and performance requirements for chemical risks.

TYPE B: Type B - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 3 chemicals at level 2 according to EN16523-1: 2015 (from 1 to 6).  
.: Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.  
J 2 > 30 mn: n-Heptane (J) CAS 142-85-5  
K 6 > 480 mn: Sodium hydroxide 40% (K) CAS 1310-73-2



Item details

Item details	Bar code	COLOUR	SIZE		
VE780BL08	3295249026011	Blue	08	120	12
VE780BL09	3295249026028	Blue	09	120	12
VE780BL10	3295249026035	Blue	10	120	12