

## Capitol II

### Double dipped chemical resistant rubber glove.

Durable rubber latex glove suitable for a wide range of applications. Double dipped for extra durability giving good protection against a range of chemicals, fats and oils. Slip resistant pattern offers enhanced grip on wet or dry items. Cotton flock lining absorbs moisture and enhances user comfort. Suitable for use with food (see separate datasheet).



### FEATURES AND TECHNOLOGY



### TYPICAL INDUSTRIES



### TECHNICAL INFORMATION

ORDER REF #	G/CAPITOL-2	
COATING MATERIAL	DUAL COATED	
PACKING	PER PACK: 10	PER CASE: 100
SIZES AVAILABLE	7-7.5, 8-8.5, 9-9.5, 10-10.5	
EU TYPE CERTIFICATION BY	SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, UK (Notified Body No. 0321)	

### CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)

EN388:2016 1010X  
EN388:2003\* 1010  
EN ISO 374-1:2016 / TYPE A AKLMPST  
EN ISO 374-5:2016

Protection against bacteria & fungi - PASS  
Protection against viruses - N/A

0120  
CAT III CE

\* X denotes not tested.  
\*\* Where applicable, EN388:2016 scores take precedent and are ongoing.  
\*\*\* There is no correlation between coupe test levels and EN ISO 1997 / TDM cut test levels.

### CERTIFICATION LEGENDS

**EN388:2016**  
Abrasion (A4) Cut (B5) Tear (C4) Puncture (D4) TDM Cut (A-F) Impact (P)

**EN ISO 374-1:2016 / TYPE A**  
A Methanol B Acetone C Acetonitrile D Dichloromethane E Carbon Disulphide F Toluene G Diethylamine H Tetrahydrofuran I Ethyl Acetate

**EN ISO 374-5:2016**  
J n-Heptane K Sodium Hydroxide (40%) L Sulphuric Acid (96%) M Nitric Acid (65%) N Ammonium Hydroxide (25%) O Hydrogen Peroxide (30%) P Hydrogen Peroxide (50%) S Hydrofluoric Acid (40%) T Formaldehyde (37%)

**EN407:2004**  
Burning Behaviour (B-4) Contact Heat (C-4) Convective Heat (C-4) Radiant Heat (C-4) Small Spillage Molten Metal (M-4) Large Quantity Molten Metal (M-4)

**EN511:2006**  
Convective Cold (C-4) Contact Cold (C-4) Water Penetration (P1)

**TYPE A** - Gloves have achieved level 2 or greater against six of the chemicals listed in EN ISO 374-1 (below). The tested chemicals are identified by their code letters under the flask pictogram.  
**TYPE B** - Achieved level 2 or greater against at least three of the chemicals.  
**TYPE C** - Achieved at least a level 1 against one of the chemicals.

\* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.  
\* Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. \* X denotes Not Tested. \* Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 1997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.  
\* For details regarding maximum permissible user exposure, see separate sheet.

### FURTHER INFORMATION

**STORAGE / TRANSPORT:** Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

**PRECAUTIONS BEFORE USE:** 1. Gloves should not be used when there is a risk of entanglement with moving machine parts. 2. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 3. The gloves should not come in contact with a naked flame or fire. 4. Do not subject to high speed or serrated blades. 5. Always read enclosed user instructions before using these gloves. 6. When used, protective gloves may provide less resistance to the dangerous chemicals due to changes in physical properties. 7. Movements, snagging, rubbing, de-gradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. 9. This product has not been tested against viruses.

**CONSTITUENTS / ALLERGIES:** Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately.

**WARNING:** This product contains natural rubber latex which may cause allergic reactions. If affected, discontinue use immediately and seek medical advice.

### FOOD TEST INFORMATION

Details of the suitability for contact with various food categories as detailed in EEC Directive are available on request. Please quote product reference when enquiring.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit: <https://www.ultimateindustrial.co.uk/product/990-Capitol-II>

If appropriate to the product, ECEU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCI customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks or registered trademarks of their respective holders. © UCI Limited, 2019

