



KEVLAR KNIT SLEEVE - Bar Tac

28643, 28645 (Yellow)

18", 22"



Certification Body: SATRA Technology Centre, Kettering, NN16 8SD, UK Notified Body: 0321
These products are classed as Personal Protective Equipment by the European PPE Directive 89/686/EEC

CAREFULLY READ INSTRUCTIONS BEFORE USE

This product is designed to provide protection against: Mechanical Risks, Thermal Risks and Welding. **No item of PPE can provide full protection - care must always be taken whilst carrying out the activity.**

EN 420:2003+A1:2009 Protective Gloves – General Requirements

Fitting & Sizing: Only wear products of a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimum level of protection.

Storage & Transport: Store the product in a well ventilated area away from extremes of temperature & strong odours.

Inspection Before & After Use: Discard and replace damage products before use. If in doubt consult manufacturer.

Cleaning: It is recommended that this product should not be washed or dry-cleaned.

EN 388:2003

Protective Gloves Against Mechanical Risks

Test	Level Achieved	Maximum Level
Abrasion Resistance	1	(4)
Blade Cut Resistance	2	(5)
Tear Resistance	4	(4)
Puncture Resistance	1	(4)

Note: Performance levels apply to the palm area of the hand.

Warning: These gloves will not prevent crushing injuries, or injuries associated with vibration. They are not to be worn when there is a risk of entanglement by moving parts of machinery.

EN 388:2003



1241