

SECTION 6 – USER INSTRUCTIONS

	<h1 style="margin: 0;">NITRILON-NCP</h1> <p style="margin: 0;">GREY NITRILE Coated Glove</p>
--	--

GLOVE SERIES: NITRILON-NCP

MARKING  ,  ,  , NITRILON-NCP, SIZE, AND 

GENERAL
 These products are classed as Personal Protective Equipment (PPE) by the European PPE Directive 89/686/EEC and have been shown to comply with this Directive through the Harmonised European Standard BS EN 388, BS EN 420.

FEATURES
 13 gauge knitted polyester with flat nitrile coating. Available in palm, knuckle or fully coated versions . These gloves are designed for precise handling with excellent grip, flexibility and dexterity. *Avoid using near moving machinery due to entanglement hazard.*

AVAILABLE STYLES
 NITRILON-NCP Fully fingered glove with Nitrile coating to palm and thumb/finger tips (PALM COATED)
 NITRILON -NCP K Fully fingered glove with Nitrile coating to palm and back to above knuckles (KNUCKLE COATED)
 NITRILON -NCP FC Fully fingered glove with Nitrile coating to full glove excluding wrist (FULLY COATED)

AVAILABLE SIZES
 6, 7, 8, 9, 10, 11

STORAGE: Gloves should be ideally stored in dry conditions in original package, away from direct sunlight.

CLEANING / MAINTENANCE
 Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. Laundering of these gloves is not recommended.

CAUTION
 These gloves have been tested to BS EN 388 and the protection referred to applies only to the palm area of the gloves. The result of the laboratory tests should help with correct glove selection, however it should be understood that the actual conditions of use cannot be directly simulated. It is therefore the responsibility of the end user and not the manufacturer to determine the gloves suitability for the intended use

OBSOLESCENCE
 When stored as recommended will not suffer change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and responsibility of user to ascertain suitability of the glove for its intended use.

<p>EN 388:2003</p> <div style="display: flex; align-items: center;">   </div> <p style="font-size: 1.2em; font-weight: bold;">4 1 2 1</p> <p style="font-size: 0.8em;">Test results are taken from the <u>palm area</u> of the gloves</p>	<p>Mechanical Risks</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Abrasion resistance</td><td style="text-align: center;">4</td></tr> <tr><td>Blade cut resistance</td><td style="text-align: center;">1</td></tr> <tr><td>Tear Resistance</td><td style="text-align: center;">2</td></tr> <tr><td>Puncture Resistance</td><td style="text-align: center;">1</td></tr> </table>	Abrasion resistance	4	Blade cut resistance	1	Tear Resistance	2	Puncture Resistance	1	
Abrasion resistance	4									
Blade cut resistance	1									
Tear Resistance	2									
Puncture Resistance	1									

These Pictograms indicate that the product protects against—**Mechanical Risks EN 388:2003.**
 The numbers indicate performance levels.

PROTECTION LIMITS
 This glove is not liquid proof. Protection against risks or hazards not mentioned in this document is not warranted. The levels of performance mentioned are ONLY valid for new gloves. The glove should not be allowed to come into contact with fire. **Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machinery.**

Tested in accordance with EN 420:2003, EN 388: 2003. EC type examinations were carried out by Satra Technology Centre, Wyndham Way, Kettering, Northants, NN16 8SD, UK, (notified body 0321)

Further information may be obtained from the address below.
ULTIMATE INDUSTRIAL
 Victoria House, Colliery Road,
 Horseley Fields, Wolverhampton
 United Kingdom WV1 2RD