▲SKYTEC Ecolridium[™]

HIGH CUT RESISTANT NITRILE FOAM COATED GLOVE WITH RECYCLED POLYESTER

Dexterous high cut resistant nitrile foam palm coated glove with 25% rPET, glass and steel fibre free, touschscreen and reinforced on the thumb crotch.

FEATURES

- > High cut resistance: Level E / ANSI A5
- 15 gauge engineered HPPE with recycled polyester (25% of liner content) offers a unique sensation of comfort and protection
- Steel and glass fibre free to avoid any risks of irritation
- Durable nitrile foam palm coating ensures good protection against abrasion and secure grip in dry, wet and oily conditions
- > Reinforced thumb crotch enhances durability
- Touchscreen capabilities to allow usage with screen devices
- > Seamless knit prevents irritation
- > RCS (Recycled Claim Standard) certified
- > 1 pair = 1 PET bottle of 500ml recycled
- > 18g of CO₂ reduced vs virgin polyester alternative





SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Logistics
- Maintenance
- Manufacturing
- Metal Industry

Suitable Applications

- Assembling
- Handling Sharp and Greasy Parts
- Machining
- Bodywork
- Precision Mechanics
- Metal Stamping

CERTIFICATION



See overleaf for explanation



∧SKYTEC Ecolridium[™]

PRODUCTION INFORMATION

MATERIALS	LINER:	15 gauge engineered HPPE, recycled polyester (25%)	
	COATING:	Nitrile foam	
COLOUR	Grey/black		
LENGTH (mm)	250 (size dependent)		
CUFF STYLE	Elasticated knit wrist		

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00048BB SKG00048BD SKG00048BF SKG00048BH SKG00048BJ SKG00048BL	10 pairs per paper wrap 120 pairs per case

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*						
0-4			0-4 Punc Resistance	Straig straig	P I Impact Resistance ght Blade Cut Resistance (EN ISO: 13997 ance	

Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE					
Measured breakthrough time	Permeation performance index (grams)				
A1	≥ 200				
A2	≥ 500				
A3	≥ 1000				
A4	≥ 1500				
A5	≥ 2200				
A6	≥ 3000				
A7	≥ 4000				
A8	≥ 5000				
Ag	> 6000				

GLOBUS

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST & AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- T: +97148829962
- F: +97148829963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com

© 2023 Globus (Shetland) Ltd | SKY-DATA-IRIDIUM-1123_1

EU Type-Examination Certificate issued by CCQS Certification Services Limited, Block 1 Blanchardstown Corporate Park, Ballycoolin Road, Blanchardstown, Dublin, D15 AKK1, Ireland (Notified Body No 2834) UKCA Type-Examination Certificate issued by CCQS UK Ltd. 25 Wilton Rd, Pimlico, London SWIV 1LW, United Kingdom. [UK Approved Body No. 1105].

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.