


 **TEGERA® INFINITY 8812**

[Learn more](#)
SOFT, FULLY DIPPED, CUT D GLOVE

Dexterous cut resistant glove, level D, suitable for assembly work. Great fit thanks to 15 gg knitted with CRF® cut resistant technology. Fully dipped with super soft nitrile foam coated palm that provides good grip on greasy and oily surfaces. Reinforced thumb crotch for improved longevity. Protection against contact heat up to 100°C. Skin friendly with Derma-test and Oeko-Tex certificate.

CHARACTERISTICS

- High level of protection
- Good fingertip sensitivity
- Good grip
- Extra comfortable
- Flexible
- Durable

FUNCTIONS

- Withstands contact heat up to 100°C
- Approved for handling foodstuffs
- Anatomically designed
- Oil and grease resistant
- Reinforcement between index finger and thumb



PREVENTS RISK OF

cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, drying out, chapping, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

cut risk environments, moist environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

fine assembly, assembly, machine operating, building and construction, carpentry, installation work, hvac installation, sheet-metal work, engineering, transport work, machine driving, warehouse work, airport work, metalwork, glass industry work, repair work, paper industry work, service work, shop work

PRIMARY INDUSTRIES OF USE

pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, mro, automotive, transportation, utilities, building and construction, logistics, facilities, service, retail

TYPE OF WORK

Medium weight

SPECIFICATION

TYPE Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

COLLECTION Infinity

LINING MATERIAL CRF® Technology, Glass fibre thread, Nylon, Spandex, 15 gg

GRIP DESIGN Foam grip pattern

COLOUR Black, Yellow

PAIRS PER: BUNDLE/CARTON 6/120

DISPLAY TYPE Bulk pack

DIPPING Fully dipped, Double-dipped

DIPPING MATERIAL Nitrile, Nitrile foam, Waterbased PU

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile


CUT RESISTANCE (EN ISO 13997) Cut resistance level D

CUT RESISTANCE (EN ISO 13997) TDM: 18.5 N

INNER MATERIAL SPECIFICATION HPPE (High performance polyethylene), Nylon, Glass fibre thread, Elastane

OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE



TP TC 019:2011



FEATURES



SIZE	ARTICLE NUMBER	EAN
6	8812-6	7340118391151
7	8812-7	7340118321769
8	8812-8	7340118321783
9	8812-9	7340118321806
10	8812-10	7340118321721
11	8812-11	7340118321745

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com