



TEGERA® 987



[Learn more](#)

Cut resistant glove, nitrile, palm-dipped, sandy finish, cut resistance level F, 7 gg, acrylic, para-aramid, stainless steel fibre yarn, Cat. II, withstands contact heat up to 250°C, extra long, water and oil repellent palm, for heavy work

CHARACTERISTICS

- Highest level of protection
- Very durable
- Good grip

FUNCTIONS

- Extra long
- Withstands contact heat up to 250°C
- Water and oil repellent palm

PREVENTS RISK OF

cut injuries, puncturing, abrasion injuries, blisters, contact with dirt, contact with moisture

PRIMARY ENVIRONMENTS OF USE

cut risk environments, warm environments, moist environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

sheet-metal work, metalwork, glass industry work, repair work

PRIMARY INDUSTRIES OF USE

glass, bricks, concrete, metal fabrication, machinery and equipment, mro

TYPE OF WORK

Heavy weight

SPECIFICATION

TYPE Cold insulation gloves, Cut resistant gloves, Heat protection gloves

CATEGORY Cat. II

LINING MATERIAL 7 gg, Acrylic, Para-aramid, Stainless steel fibre yarn

GRIP DESIGN Sandy finish

COLOUR Black, Yellow

PAIRS PER: BUNDLE/CARTON 6/60

DISPLAY TYPE Bulk pack

DIPPING Palm-dipped

DIPPING MATERIAL Nitrile

CUFF STYLE Extended knitwrist cuff

CUFF MATERIAL Textile

CUT RESISTANCE (EN ISO 13997) Cut resistance level F

CUT RESISTANCE (EN ISO 13997) TDM: 30.3 N


INNER MATERIAL SPECIFICATION Acrylic, Para-aramid, Stainless steel fibre yarn, Polyester

OUTER MATERIAL SPECIFICATION Nitrile

COMPLIANCE



TP TC 019:2011



FEATURES



SIZE	ARTICLE NUMBER	EAN
7	987-7	7340118340289
8	987-8	7340118340371
9	987-9	7340118340463
10	987-10	7340118340555
11	987-11	7340118340647

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com