Magnesium- NS75 **BRG153**



USER INFORMATION

This product is compliant with the mentioned harmonised standard and PPE Regulation 2016/425. **Declaration of Conformity:**

The EU Declaration of Conformity can be found at www.blackrockworkwear.com/doc

Performance and Limitation of use:

Performance levels are applicable to the whole glove.

This glove has a high tear resistance and should not be worn where there is a risk of entanglement in moving machinery.

X: indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

0: indicates the glove falls below the minimum performance level for the given individual-hazard.

Sizing:

7/S - 11/2XL

Inspection before and after use:

Before use, inspect the glove for any defects or imperfections.

Storage:

Store in a dry, cool place away from direct sunlight.

Cleaning:

Clean with a damp cloth to remove excess contamination. Performance levels may be affected by laundering.

Date of Obsolescence:

If stored correctly, the mechanical properties will not change. The glove's lifespan cannot be specified as it depends on the applications and the user.



ISO Cut Resistance Puncture Resistance Tear Resistance Blade Cut Resistance Ahrasion Resistance

Safety Rating Guide	Level 1	Leve 2	4	Level 3	ľ	Level 4	Level 5
Abrasion	100	500	1	2000		8000	N/A
Cut (Coupe Test)	1.2	2.5	2.5 5.0		10.0		20.0
Tear	10	25	5 50		Г	75	N/A
Puncture	20	60	Т	100		150	N/A
Level	. A	В	С	1	,	E	F
Cut (ISO)	2	5	10	1	5	22	30

Testing provided by CTC 4, rue Hermann Frenkel 69367 Cedex 07 France Notified Body no.0075

www.blackrockworkwear.co.uk

Blackrock is a registered trademark of Rodo Limited All rights reserved Rodo Limited, Lumb Lane, Drovisden Greater Manchester, M43 7BU