

PCP-WH

White PU palm coating on a white polyester shell.

A 13 gauge, light weight, machine knitted seamless construction polyester liner with a tough polyurethane coating on the front face. Excellent dexterity and grip combined with improved mechanical protection.



FEATURES AND TECHNOLOGY



LIGHT
WEIGHT



LOW
LINTING



HIGH
DEXTERITY



PU

TYPICAL INDUSTRIES



GENERAL
PURPOSE



PRECISION
HANDLING



PRODUCT
PROTECTION



LOGISTICS &
WAREHOUSING



PAINTING &
DECORATING

TECHNICAL INFORMATION

ORDER REF #	G/PCP-WH	
COATING MATERIAL	PU	
PACKING	PER PACK: 10	PER CASE: 240
SIZES AVAILABLE	6 (XS), 7 (S), 8 (M), 9 (L), 10 (XL)	
EU TYPE CERTIFICATION BY	SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, UK (Notified Body No. 0321)	

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)



3 1 3 1 X
Abrasion (D4)
Cut (D5)
Tear (D6)
Puncture (D7)
TDM Cut (A-F)



4 1 3 1
Abrasion (D4)
Cut (D5)
Tear (D6)
Puncture (D7)

¹ 'X' denotes not tested.

² Where applicable, EN388:2016 scores take precedent and are ongoing.

³ There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.

CAT II CE

CERTIFICATION LEGENDS

EN388:2016



Abrasion (D4)
Cut (D5)
Tear (D6)
Puncture (D7)
TDM Cut (A-F)
Impact (H)

EN388:2016 Blade Cut TDM EN ISO 13997¹



¹ For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

NEWTON	LEVEL
> 30	F
> 22	E
> 15	D
> 10	C
> 5	B
> 2	A

EN407:2004



Burning Behaviour (D4)
Contact Heat (D5)
Convective Heat (D6)
Radiant Heat (D7)
Small Splashes Molten Metal (D8)
Large Quantity Molten Metal (D9)

EN511:2006



Corrosive Cold (D4)
Corrosive Cold (D5)
Water Penetration (D6)

¹ For details regarding maximum permissible user exposure, see separate sheet.

¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit:
<https://www.ultimateindustrial.co.uk/product/1047-PCP-WH>

If appropriate to the product, ECEU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address or by contacting UCI customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks or registered trademarks of their respective holders. © UCI Limited, 2018



Phone: +44 (0)1902 451 451
Fax: +44 (0)1902 451 271
Email: sales@ultimateindustrial.co.uk
Web: www.ultimateindustrial.co.uk



Ultimate
Industrial

Leadership in
PROTECTION.™

© 2018, Ultimate Cleaners (Industrial) Ltd.
Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK
Registered in England No. 2035621



Phone: +44 (0)1902 451 451
Fax: +44 (0)1902 451 271
Email: sales@ultimateindustrial.co.uk
Web: www.ultimateindustrial.co.uk



Ultimate
Industrial

Leadership in
PROTECTION.™

© 2018, Ultimate Cleaners (Industrial) Ltd.
Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK
Registered in England No. 2035621