




SOUTHCOMBE
BROTHERS



Firemaster[®] Debris Glove

DESCRIPTION and USE

A basic gunn cut glove used for a multitude of tasks wherever hazardous objects pose a risk. Pyrohide[®] leather is used on the palm and re-inforcement patches on the back of the fingers and across the back of the knuckles. A hardwearing cotton fabric back and a knitted acrylic cuff complete the exterior. The glove has a seamless knitted lining made from a Kevlar[®] yarn with a glass fibre core. It has been designed to offer the wearer a high degree of protection against heat and fire, water, oil, chemicals, cuts and abrasions. It is manufactured in accordance with EN420 for fit and dexterity, EN388 for mechanical risks and under EN407 for thermal risks it achieves a level 1 for contact heat.

LEATHER SPECIFICATIONS

PYROHIDE[®] is a world class top-grade grain cowhide leather developed specifically for fire-fighters and used by 42 of the 58 brigades in the UK. It offers resistance to fire, heat, water, salt water, liquid chemicals (sulphuric acid, hydrochloric acid, caustic soda, ethanol etc) and Man Made Mineral Fibers (MMMFs). It is highly tactile in wet and dry conditions and dries soft following normal use. Manufactured in the UK by Southcombe Brothers using a proprietary formula, it is exclusive to Southcombe Brothers. PYROHIDE[®] is the first line of defence for fire-fighters.



BACK OF HAND

Hard wearing cotton zein (200 gms/m²)

LINING

Seamless knitted KEVLAR[®] with glass-fibre core providing high levels of abrasion resistance and un-paralleled levels of cut/slash resistance. The lining is plated with a Viloft[™] yarn to wick moisture away from the hand.



CUFF

100% knitted acrylic to create snug closure around wrist.



- Manufactured in accordance with EN388: Mechanical Risks
- Certified to level 1 for Contact Heat Resistance under EN407: Thermal Risks
- PYROHIDE[®] leather palm – the No. 1 choice for UK fire-fighters
- Level 5 slash resistant blended KEVLAR[®] seamless knitted lining
- Tough cotton fabric back
- Over 165 years of glove manufacturing experience
- Sizes : XXS, XS, S, M, L, XL, XXL.

Southcombe Brothers Ltd
Stoke-sub-Hamdon
Somerset TA14 6QD
UK

Phone: +44 (0) 1935 823567
Fax: +44 (0) 1935 822918
E-mail: sales@southcombe.com
www.southcombe.com

Firemaster Debris Glove

TEST RESULTS

PROPERTY	LEVEL	METHOD	PROPERTY	LEVEL	METHOD
Abrasion Resistance	3 (1 min, 4 max)	EN388	Tear Resistance	4 (1 min, 4 max)	EN388
Blade/Cut Resistance	5 (1 min, 5 max)	EN388	Puncture Resistance	3 (1 min, 4 max)	EN388
Dexterity	Pass	EN420	Contact Heat	1	EN407

GLOVE CARE AND MAINTENANCE

Gloves that are deemed non-repairable are to be disposed of when damaged. Gloves do not require the use of specialist solvent-based products for cleaning or maintenance and these should not be used under any circumstances. The design and materials used ensure that the user can maintain the gloves in hygienic condition. PYROHIDE® is easy to clean and quick to dry. The leather also stays soft and dextrous after being wetted.

For best results follow this procedure:

- Produce a good lather in lukewarm water using mild detergent of neutral pH.
- Immerse the gloves and wash gently on your hands.
- Remove gloves and rinse thoroughly in clean water.
- Squeeze out all excess water from the fingers downwards and pull gently into shape.
- Hang to dry away from direct sunlight or heat.
- Wash gloves before they become too soiled.
- A sponge not a stiff brush is recommended to be used for ingrained grime.
- Gloves may be washed with articles of a similar colour provided the above instructions are followed.



Southcombe Brothers Ltd

Stoke-sub-Hamdon

Somerset TA14 6QD

UK

Phone: +44 (0) 1935 823567

Fax: +44 (0) 1935 822918

E-mail: sales@southcombe.com

www.southcombe.com