

Vega™

30cm Latex gauntlet with cotton flock lining

Lightweight but durable natural rubber gloves with a cotton flock lining to increase comfort and help absorb perspiration. Embossed Powergrip™ honeycomb coating acts to improve grip in wet and dry conditions whilst maintaining extra sensitivity and overall dexterity. Anatomically shaped to ensure comfort, flexibility and to reduce hand fatigue during prolonged periods of use. A rolled cuff offers drip protection, increased glove strength when donning and helps reduce roll-down.



FEATURES AND TECHNOLOGY



TYPICAL INDUSTRIES



TECHNICAL INFORMATION

ORDER REF #	G/VEGA	
COATING MATERIAL	N/A	
PACKING	PER PACK: 10	PER CASE: 100
SIZES AVAILABLE	7-7.5, 8-8.5, 9-9.5, 10-10.5	
EU TYPE CERTIFICATION BY	SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, UK (Notified Body No. 0321)	

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)

1 0 1 0 X **1 0 1 0** **KLMPST**

Abrasion (A4) Cut (B3) Tear (C4) Puncture (D4) TDM Cut (A-F)
 Abrasion (A4) Cut (B3) Tear (C4) Puncture (D4)

Protection against bacteria & fungi - **PASS**
 Protection against viruses - **N/A**

0120
 CAT III

¹ 'X' denotes not tested.
² Where applicable, EN388:2016 scores take precedent and are ongoing.
³ There is no correlation between couple test levels and EN ISO 15997 / TDM cut test levels.

CERTIFICATION LEGENDS

EN388:2016

EN ISO 374-1:2016 / TYPE A

EN ISO 374-5:2016

TYPE A - Gloves have achieved level 2 or greater against six of the chemicals listed in EN ISO 374-1 (below). The tested chemicals are identified by their code letters under the flask pictogram.
TYPE B - Achieved level 2 or greater against at least three of the chemicals.
TYPE C - Achieved at least a level 1 against one of the chemicals.

A	Methanol	J	n-Heptane
B	Acetone	K	Sodium Hydroxide (40%)
C	Acetonitrile	L	Sulphuric Acid (96%)
D	Dichloromethane	M	Nitric Acid (65%)
E	Carbon Disulphide	N	Ammonium Hydroxide (25%)
F	Toluene	O	Hydrogen Peroxide (30%)
G	Diethylamine	P	Hydrogen Peroxide (50%)
H	Tetrahydrofuran	S	Hydrofluoric Acid (40%)
I	Ethyl Acetate	T	Formaldehyde (37%)

EN407:2004

EN511:2006

* For details regarding maximum permissible user exposure, see separate sheet.

¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between couple test levels and ISO 15997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational purposes only.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Gloves should not be used when there is a risk of entanglement with moving machine parts. 2. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 3. The gloves should not come in contact with a naked flame or fire. 4. Do not subject to high speed or serrated blades. 5. Always read enclosed user instructions before using these gloves. 6. When used, protective gloves may provide less resistance to the dangerous chemicals due to changes in physical properties. 7. Movements, snagging, rubbing, de-gradation caused by the chemical contact etc. may reduce the actual use time significantly. For corrosive chemicals, degradation can be the most important factor to consider in selection of chemical resistant gloves. 9. This product has not been tested against viruses.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately.

WARNING: This product contains natural rubber latex which may cause allergic reactions. If affected, discontinue use immediately and seek medical advice.

For more information about this product, or to access the Declaration of Conformity or Product Certification, visit: <https://www.ultimateindustrial.co.uk/product/991-Vega>

If appropriate to the product, ECEU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCI customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks™ or registered® trademarks of their respective holders. © UCI Limited, 2018



Phone: +44 (0)1902 451 451
Fax: +44 (0)1902 451 271
Email: sales@ultimateindustrial.co.uk
Web: www.ultimateindustrial.co.uk



© 2018, Ultimate Cleaners (Industrial) Ltd.
 Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK
 Registered in England No. 2035621



Phone: +44 (0)1902 451 451
Fax: +44 (0)1902 451 271
Email: sales@ultimateindustrial.co.uk
Web: www.ultimateindustrial.co.uk



© 2018, Ultimate Cleaners (Industrial) Ltd.
 Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK
 Registered in England No. 2035621