

Adept®-RED-FC

NFT® fully coated gloves with red liner

Red Nylon and Lycra blend liner providing one of the most comfortable and supportive gloves on the market. Patented NFT® full coating, specially developed for when precision handling is required, produces unrivalled grip on dry, wet and oily conditions. Provides class leading abrasion resistance greater than 25,000 cycles. Certified to the Oeko-Tex® standard 100 for environmentally friendly textiles. Enhanced breathability working in conjunction with the Sanitized® hygiene function provides prolonged freshness, protection and outstanding wearer comfort over heavily extended uses.



OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100

FEATURES AND TECHNOLOGY




TYPICAL INDUSTRIES



TECHNICAL INFORMATION

ORDER REF #	G/ADEPT-FC-RED	
COATING MATERIAL	NITRILE, NFT®	
PACKING	PER PACK: 10	PER CASE: 120
SIZES AVAILABLE	7 (S), 8 (M), 9 (L), 10 (XL), 11 (2XL)	
EU TYPE CERTIFICATION BY	SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (Notified Body No. 2777)	

CERTIFICATION AND STANDARDS (SEE OVERLEAF FOR FURTHER DETAILS)



* X denotes not tested.
¹ Where applicable, EN388:2016 scores take precedent and are ongoing.
² There is no correlation between coupe test levels and EN ISO 13997 / TDM cut test levels.

CERTIFICATION LEGENDS

EN388:2016

Abraction (A4)	□
Cut (B5)	□
Tear (C4)	□
Puncture (D4)	□
TDM Cut (A-F)	□
Impact (I)	□

EN388:2016 Blade Cut TDM EN ISO 13997*

NEWTON	LEVEL
≥ 30	F
≥ 22	E
≥ 15	D
≥ 10	C
≥ 5	B
> 2	A

* For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

EN407:2004

Burning Behaviour (B4)	□
Contact Heat (C4)	□
Convective Heat (C4)	□
Radiant Heat (C4)	□
Small Splashes Molten Metal (C4)	□
Large Quantity Molten Metal (C4)	□

EN511:2006

Convective Cold (C4)	□
Contact Cold (C4)	□
Water Penetration (C4)	□

* For details regarding maximum permissible user exposure, see separate sheet.

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately. This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

*SANITIZED® TREATMENT

Sanitized®: These gloves incorporate a Biocidal product. The Biocidal treatment protects against a broad spectrum of Bacteria and Fungi. The active Biocidal substance - Zinc Pyrithione - promotes freshness and inhibits odours.



For more information about this product, or to access the Declaration of Conformity or Product Certification, visit: <https://www.ultimateindustrial.co.uk/product/807-Adept-RED-FC>

If appropriate to the product, ECEU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCI customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCI are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCI assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks™ or registered® trademarks of their respective holders. © UCI Limited, 2019



Phone: +44 (0)1902 451 451
 Fax: +44 (0)1902 451 271
 Email: sales@ultimateindustrial.co.uk
 Web: www.ultimateindustrial.co.uk



© 2019, Ultimate Cleaners (Industrial) Ltd.
 Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK
 Registered in England No. 2035621



Phone: +44 (0)1902 451 451
 Fax: +44 (0)1902 451 271
 Email: sales@ultimateindustrial.co.uk
 Web: www.ultimateindustrial.co.uk



© 2019, Ultimate Cleaners (Industrial) Ltd.
 Victoria House, Colliery Road, Wolverhampton, WV1 2RD, UK
 Registered in England No. 2035621