


# USER INSTRUCTIONS

**Blackrock**<sup>®</sup>

STYLE: 5401000 & 84301

Performance:


in accordance with EN388: abrasion/blade cut/tear/puncture



**4.1.3.1.X**



## EN 420 / 388 - Suitable for medium mechanical risks (CE Cat.2)

Store in a dry cool (5°-25°C) dark place. Cleaning with commercially available cleaning material (e.g. Brushes, Cloths) is recommended. For washing or dry-cleaning a specialised cleaner must be consulted. Ensure that the gloves are intact before using them. Do not use damaged gloves or gloves with changed properties. No shelf life can be given as this depends on the degree of wear caused by the mode of use and field of application. Use only for minimum risks. Unused/unstressed gloves: 



**4 1 3 1 X**

— Puncture Resistance  
— Tear Resistance  
— Blade Cut Resistance  
— Abrasion Resistance

LEVEL	1	2	3	4	5
Abrasion Resistance No. of cycles	100	500	2000	8000	-
Blade Cut Resistance	1.5	2.5	5	10	20
Tear Resistance	10	25	50	75	-
Puncture Resistance	20	60	100	150	-

EN 388	EN 420	WASHABLE
✓	✓	X

The individual test results are printed onto the gloves.

**Attention: The test results only refer to the reinforced/coated parts of the glove**

Please contact Rodo Limited for further information.

They have been subject to a CE examination performed by:

CTC-Le CENTRE TECHNIQUE CUIR CHAUSSURE MAROQUINERIE  
4 Rue Hermann Frenkel 69367 LYON CEDEX 07 FRANCE  
Notified Body Number 0075

Note! That no PPE can provide full protection, so always carry out task/activity with highest care.

Rodo Limited  
Lumb Lane, Droylsden,  
Greater Manchester M43 7BU  
T: +44 (0)161 371 6400  
F: +44 (0)161 371 6401  
W: [www.rodo.co.uk](http://www.rodo.co.uk)