

## **FBN49**

### **WORKS IN DRY ENVIRONMENT**

Mechanical leather glove, the American cut prevents the seams from being uncomfortable on the underside of the hand



### **Applications**

- Public works
- Building
- Finishing works / Craftsmanship
- Maintenance
- Automotive
- Temporary work

## **Certifications and norms**



# **Protects against risks**









## **FBN49**

#### **WORKS IN DRY ENVIRONMENT**

Mechanical leather glove, the American cut prevents the seams from being uncomfortable on the underside of the hand

### **Standards - Details**



#### EN388:2016+A1:2018

3 [0-4] ABRASION RESISTANCE 1 [0-5] CUT RESISTANCE 2 [0-4] TEAR RESISTANCE 2 [0-4] PIERCE RESISTANCE X [A-F] CUT RESISTANCE ISO 13997

### **Technical details**

Glove kind	Mechanical glove
Glove family	Cut and sewn leather palm / leather back
Mechanical glove kind	Cut and sewn
Thickness	0,9 -> 1,1 mm
Cuff caracteristic	Sewn open cuff with elastic
Benefits element	Vendor pack
Color	Natural
Size	7, 8, 9, 10, 11
Type of packaging	Pack of 12







## **FBN49**

### **WORKS IN DRY ENVIRONMENT**

Mechanical leather glove, the American cut prevents the seams from being uncomfortable on the underside of the hand

Logistics information									
Reference	Colour	Size	Designation	EAN13	Box code	Multiple sales	Minimum sales	Weight	
FBN4907	Natural	07	FBN49	3295249158477	13295249158474	120	12	12.0 kg	
FBN4908	Natural	08	FBN49	3295249039820	13295249039827	120	12	13.5 kg	
FBN4909	Natural	09	FBN49	3295249018009	13295249018006	120	12	15.2 kg	
FBN4910	Natural	10	FBN49	3295249018016	13295249018013	120	12	15.4 kg	
FBN4911	Natural	11	FBN49	3295249039837	13295249039834	120	12	20.7 kg	



