

SECTION 7 –USER INFORMATION AND PRODUCT MARKING

USER INFORMATION



Product reference: Comfort Fit Gloves **Glove sizes available:** 7,8,9,10,11

Manufacturer:
Le Mark Group Ltd
Unit 1, Houghton Hill Industries
Sawtry Way
Houghton
Cambridgeshire
PE28 2DH
United Kingdom

Notified Body responsible for certification:
SATRA Technology Europe Ltd,
Bracetown Business Park,
Clonee,
Co. Meath
D15 YN2P
Ireland

Glove Designation

These gloves are designed to protect the palm of the hands against abrasion created by the handling of ropes.

These Gloves are classed as Personal Protective Equipment (PPE) by the European PPE Regulation (EU) 2016/425 and have been shown to comply with this Regulation through the Harmonized European Standard(s) EN388:2016 EN 420: 2003 + A1: 2009

Performance and limitation of use

This product has been tested in accordance with EN388:2016 EN 420:2003+A1:2009

Do not use near machinery or moving parts (entanglement hazard)

Gloves do not protect against thermal or chemical hazards

Gloves should not be used to protect against cut hazards or sharp edges

Inspect gloves for damage and imperfections before use, do not use damaged gloves

Information regarding protection refers to the working surface, i.e. 'the palm' of the glove, which has been submitted to testing.

The protection levels indicated are only valid for new gloves.

Storage

When not in use, store the product in a well-ventilated area away from damp

Keep out of direct sunlight, in a cool dry place


Cleaning and Maintenance

These gloves should not be washed, laundered or ironed

New and used gloves should be thoroughly inspected for damage before use.

EU Declaration of conformity can be accessed at: www.dirtyrigger.com/doc/comfortfit

USER INFORMATION – Dirty Rigger Rope Ops Gloves

<p>Tested in accordance with</p> <p>EN388:2016</p>  <p>2021X</p>		Level
	Abrasion resistance	2
	Blade cut resistance	0
	Tear resistance	2
	Puncture resistance	1
	TDM Cut resistance	X

'X' Indicates no test conducted / '0' indicates no score achieved during test

EN388:2016 Levels are based upon the table below:

Performance Level	1	2	3	4	5	
6.1 Abrasion resistance (cycles to failure)	100	500	2000	8000	N/A	
6.2 Blade cut resistance (minimum cut resistance index)	1.2	2.5	5.0	10	20	
6.4 Tear resistance (lowest peak force / N)	10	25	50	75	N/A	
6.5 Puncture resistance (lowest peak force / N)	20	60	100	150	N/A	
6.6 TDM Cut Resistance (Force N)	Level A	Level B	Level C	Level D	Level E	Level F
	2	5	10	15	22	30

Sizing BS EN 420:2003 + A1: 2009

Size	Size no.
S	7
M	8
L	9
XL	10
XXL	11