



TEGERA® 8155T

Leather glove, 0,6 - 0,8 mm full grain goatskin of top quality, Cat. II, black, reinforced index finger, for touchscreen, water repellent leather, elasticated 180°, for allround work

PROPERTIES

High level of protection, extremely good fingertip sensitivity, extra flexible, very durable, perfect fit

SPECIFICATION

TYPE OF GLOVE Special protection work gloves

CATEGORY Cat. II

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

THICKNESS 0,6 - 0,8 mm

DEXTERITY 5

FASTENING Elasticated 180°

LENGTH RANGE 230-265 mm

COLOUR Black

PAIRS PER PACKAGE/CARTON 3/60

DISPLAY Thread

OUTER MATERIAL SPECIFICATION Leather, natural latex

SIZE	ART. NO.	EAN NO.
6	8155T-6	7340118376851
7	8155T-7	7340118376943
8	8155T-8	7340118377032
9	8155T-9	7340118377124
10	8155T-10	7340118377216
11	8155T-11	7340118377308
12	8155T-12	7340118377391

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 8155T

FEATURES

For touchscreen, water repellent leather

PREVENTS RISK OF

Prevents risk of, blisters, grazes, scratches, lacerations, contact with dirt, contact with damp

PRIMARY ENVIRONMENTS OF USE

Moist environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Security- and police work

PRIMARY INDUSTRIES OF USE


Service

TYPE OF WORK

Medium weight



CE Cat. II

EN 420:2003 + A1:2009  EN 388:2016 2011X EN ISO 11640:2018



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-11-08

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8155T

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	0	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016 EN ISO 11640:2018
2011X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2021-11-08

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com