




4021X SIZE: 8/M



MADE IN VIETNAM



Cut



Puncture




Abrasion



Impact



Fluid Grip



ISEA
CUT: 5

CE
4544

Impact
Protection

SuperFabric®
Protection Zone

GGT5® HexArmor Mud Grip® 4021X

FIBER CONTENT:

Shell: 57% Nylon, 18% Polyurethane, 11% Neoprene, 8% PVC, 2% Cotton, 2% EVA Foam, 1% Polyester, 1% Spandex

Thermal Plastic Rubber

Lining: 54% Cotton, 26% Plastic, 20% Polyester

HX34

WARNING This product is cut & puncture resistant but NOT cut and puncture PROOF. DO NOT USE WITH MOVING OR SERRATED BLADES OR TOOLS. Always conduct a safe test to make sure it is suited for your use.

HexArmor® is a registered trademark of Performance Fabrics, Inc.
SuperFabric® is a registered trademark of HDM, Inc.

Protected by patents and patents pending

Call 1.877.MYARMOR or visit hexarmor.com

HexArmor
ELITE with SuperFabric.



HexArmor Mud Grip® 4021X

User Information

CE USER INFORMATION 4021X – HEXARMOR® GGT5® MUD MECHANIC'S STYLE

GLOVE DESCRIPTION

Heavy duty mechanic's style glove for the oil and gas industry. The gloves can be used in industry applications where cut resistance and oil grip is needed. But gloves are not to be used with moving or serrated blades and are cut resistant, not cut proof. Protection areas includes palm, with impact protection on the back of hand. Protection levels below are measured on protection area from palm area of glove.

EN420: 2003 SIZE/STYLE GUIDE HAND SIZE – DEFINED IN EN 420: 2003 4021X – GGT5® MUD SIZE

7	S/7
8	M/8
9	L/9
10	XL/10
11	XXL/11
12	3XL/12

All sizes comply with the EN420:2003 test for comfort and fit and dexterity. Per customer recommendations, HexArmor® has specifically manufactured these gloves for special purpose therefore the length is appropriate for the intended use.

EN388: 2003 INTERMEDIATE SAFETY CATEGORY TESTED IN ACCORDANCE WITH EN 388:2003



MECHANICAL DATA

Abrasion resistance	level 4
Blade cut resistance	level 5
Tear resistance	level 4
Puncture test	level 4

ANSI PUNCTURE

Tested in accordance with Clause 6.4 of EN 388:2003 Level 5

OTHER TESTS:

Gloves have been tested and approved in the following:
BS EN14362: 2003 part 2 Determination of certain Azo colorants in Textiles (with extraction)
Gloves received "pass" on all tests above

MARKING ON GLOVE

Name of Manufacturer, model number, size, CE mark, EN388:2003 pictogram, "book" symbol, product name.

STORAGE

Gloves should be ideally stored in dry conditions in original package.

OBSOLESCENCE

When stored as recommended will not suffer change in mechanical properties for up to five years from the date of manufacture. Service life cannot be specified and depends on application and responsibility of user to ascertain suitability of the glove for its intended use.

GENERAL

The products are manufactured under a quality system. None of the raw materials or processes used in the manufacture of these products is known to have any harm on the wearer.

EC TYPE EXAMINATION CARRIED OUT BY:

SATRA Technology Centre Ltd, SATRA House
No 0321
Wyndham Way Telford Way,
Kettering, Northants
NN16 8SD
Tel: +44 (0) 1536 410000
Fax: +44 (0) 1536 410626

NOTE

The information contained herein is intended to assist the wearer in selection of Personal Protective Equipment. The results of physical tests should also help in glove selection. However, it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the user not the manufacturer to determine the glove suitability for the intended use.

WARNING

Do not use with moving or serrated blades.

FURTHER INFORMATION AVAILABLE AT:

Ref: 4021X – GGT5® Mud

USA	CANADA	EUROPE
1-877-692-7667	1-616-459-4144	1-877-692-7667
1-616-459-4144		

HexArmor
2000 Oak Industrial Drive NE
Grand Rapids, MI 49505
hexarmor.com

Call 1.877.MYARMOR or visit hexarmor.com

HexArmor
ELITE  WITH SuperFabric.