

# KEYLAR SAFETY GLOVES USER INFORMATION

## GLOVE DESCRIPTION

The gloves are a machine knitted liner made from 100% Kevlar® yarn with an elasticated wristing to assist in ventilation and comfort. These gloves provide good resistance against abrasion in dry handling conditions Not for use with liquids.

## GLOVE SERIES

KKH7 Machine Knit Gloves

## MARKING



STYLE, SIZE AND



| GLOVE SIZES AVAILABLE       |             |
|-----------------------------|-------------|
| Hand Size defined in EN 420 | Glove Sizes |
| 6                           | X-Small     |
| 7                           | Small       |
| 8                           | Medium      |
| 9                           | Large       |
| 10                          | X-Large     |
| 11                          | XX-Large    |

## INTERMEDIATE SAFETY CATEGORY

## CAT II

### Mechanical test data in accordance with EN 388

|          |            |       |   |
|----------|------------|-------|---|
| Abrasion | Resistance | Level | 1 |
| Cut      | Resistance | Level | 4 |
| Tear     | Resistance | Level | 4 |
| Puncture | Resistance | Level | X |

EN 388



144X

This Pictogram indicates that the product protects against Mechanical risks and complies under EN 388. The numbers indicate performance levels.

**Note: Do not use near moving machines if there is a risk of entanglement**



The results are taken from the palm area of the gloves

All EC type examinations were carried out by SGS United Kingdom Ltd.  
Weston-super-Mare, BS226WA, UK (Notified Body No. 0120) in  
accordance with EU Directive 89/686/EEC

## CLEANING / MAINTENANCE

Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. If appropriate, decontamination may take place under lukewarm water using laundry soap and detergent. Don't use chlorine bleaches.

**NOTE!** *The performance characteristics of worn and laundered gloves may differ from the results shown above.*

## STORAGE

Gloves should be ideally stored in dry conditions in original package and out of direct sunlight.

## OBSOLESCENCE

When stored as recommended will not suffer change in mechanical properties for up to three years from the date of manufacture. Service life cannot be specified and depends on the application and responsibility of user to ascertain suitability of the glove for its intended use.

## GENERAL

The gloves and the raw materials used in their manufacture are not shown to be harmful to the wearer. The information contained herein is intended to assist the wearer in the selection of personal protective equipment.

## PLEASE NOTE

The results of the physical tests should also help in glove selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the user not the manufacturer to determine glove suitability to the intended use.

Further information may be obtained from the manufacturer.

**ULTIMATE INDUSTRIAL LTD.**  
**VICTORIA HOUSE, COLLIERY**  
**ROAD, HORSELEY FIELDS**  
**WOLVERHAMPTON WV1 2RD, U.K**