

**38-514** Excellent chemical resistance including solvents or strong acids

Previously known as: ChemTekTM 38-514

# Our thinnest butyl gloves, delivering superior chemical resistance, dexterity and comfort

- Advanced defenses: AlphaTec<sup>®</sup> 38-514 butyl gloves offer superior protection against highly aggressive chemicals, including aldehydes, ketones, esters and concentrated mineral acids
- **Reduced allergy risks:** As they are free from latex proteins, these hand protection gloves present no risk to wearers with latex allergies
- Improved ergonomics: Designed for comfort, AlphaTec<sup>®</sup> 38-514 industrial gloves feature a naturally curved shape and a soft feel, protecting hands while facilitating donning and doffing
- Enhanced flexibility: Their soft butyl formulation also enhances their flexibility and dexterity
- Strengthened grip: In addition, these butyl gloves feature a rough finish around the hand section, enhancing grip and ensuring safer handling

#### Industries

- Automotive
- Life Sciences
- Chemical

#### Applications

- Equipment repair & maintenance
- Loading and unloading of proces equipment
- Handling incoming goods
- Filling, blending and charging of raw materials
- Transferring liquids and solids
- Opening and draining pumps valves or lines
- Transferring liquids and solids between vessels and tanks and process equipment
- Supervision of running operation
- Charging and blending raw materials
- Opening furnaces draining pumps valves or lines and crackers BTX process
- Cleaning furnaces, distillation pumps, valves or lines and crackers BTX process
- Unexpected leakages spills or other releases







## 38-514 **Excellent chemical resistance including** solvents or strong acids

#### Previously known as: ChemTekTM 38-514

#### **Key Features**

- Butyl polymer: Resistance against the most aggressive chemicals\*
- Latex-free formulation: No risk of latex-related allergic reactions
- Ergonomic design and soft feel: Form-fitting comfort and protection

\*including aldehydes, ketones, esters and concentrated mineral acids

• Product tested to and confirms to the requirements of EN 16350. Inclusion of EN16350 into product certification still pending

#### **Vulcanization Chemical Accelerators**

- 2-Mercaptobenzothiazole disulfide
- Dipentamethylene thriuram disulfide
- Tetramethylthiuram disulfide

Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.

#### **Performance Standards**



### **Specifications**

BRAND   STYLE	DESCRIPTION	SIZE	LENGTH	COLOR	PACKAGE
AlphaTec <sup>®</sup> 38-514	Butyl Polymer,	7, 8, 9, 10, 11	350 / 13.8	Black	<ul> <li>36 pairs in a carton; individually wrapped with insert</li> <li>Size 11 unavailable in Canada and USA</li> </ul>

Europe, Middle East & Africa Region

Ansell Healthcare Europe NV Ansell Healthcare Europ Riverside Business Park Blvd International, 55 1070 Brussels, Belgium T: +32 (0) 2 528 74 00 F: +32 (0) 2 528 74 01

**Canada** Ansell Canada Inc. Ansell Canada Inc. 105, rue Lauder Cowansville (Québec) J2K 2K8, Canada T: 1 800 363-8340 F: 1 888 267-3551 North America Region Ansell Healthcare Products LLC 111 Wood Avenue South,

Suite 210 Iselin, NJ 08830, USA T: +1 800 800 0444 F: +1 800 800 0445

#### Latin America & Caribbean Region

Ansell Commercial Mexico S.A de C.V Blvd. Bernardo Quintana No. 7001-C Blvd. Bernardo Quintana No. 70 Q7001 Torre II. Suites 1304, 1305 y 1306. Col. Centro Sur, c.p. 76079 Queretaro, Qro. Mexico T: +52 442 248 1544 / 248 3133

Ansell, <sup>®</sup> and <sup>™</sup> are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2021 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application



