

Harpon 319

DESCRIPTION AND GENERAL PROPERTIES

- **Material** Natural latex
- **Length (cm)** 25-27
- **Thickness (mm)**
- **Wrist** Knitted wrist
- **Colour/Color** Orange
- **Interior finish** Textile support
- **Exterior finish** Reinforced grip
- **Size / EAN** 7 8 9
- **Packaging** 1 pair/bag - 5 pairs/box - 50 pairs/carton
- **Complementary information** Guaranteed without DMF
Guaranteed without silicone



PERFORMANCE RESULTS

Certification category 2



X1XXXX



3131X

Legends

ANSI CUT RESISTANCE

A1	≥ 200 G	A4	≥ 1500 G	A7	≥ 4000 G
A2	≥ 500 G	A5	≥ 2200 G	A8	≥ 5000 G
A3	≥ 1000 G	A6	≥ 3000 G	A9	≥ 6000 G

EN 511 COLD HAZARDS

PERFORMANCE LEVELS	0-4	0-4	0 or 1
Water permeability			
Contact cold resistance			
Convective cold resistance			

EN 407 THERMAL RISKS Heat and fire

PERFORMANCE LEVELS	0-4	0-4	0-4	0-4	0-4	0-4
Resistance to large quantities of molten metal						
Resistance to small drops of molten metal						
Radiant heat resistant						
Convective heat resistance						
Contact heat resistance						
Burning behaviour						

PROTECTION FROM PESTICIDES

ISO 18889	ISO 18889	ISO 18889
G1	G2	GR

MICRO-ORGANISMS

EN ISO 374-5	EN ISO 374-5
Protection against bacteria, fungi	Protection against bacteria, fungi, virus

EN 388 MECHANICAL HAZARDS

PERFORMANCE LEVELS	0-4	0-5	0-4	0-4	A-F (P)
Impact protection					
Cut resistance according to ISO 13997					
Puncture resistance					
Tear resistance					
Blade cut resistance					
Abrasion resistance					

CHEMICAL RISKS

EN ISO 374-1 Type A	EN ISO 374-1 Type B	EN ISO 374-1 Type C
U V W X Y Z	X Y Z	
A Methanol	J n-Heptane	
B Acetone	K Sodium hydroxide 40%	
C Acetonitrile	L Sulphuric acid 96%	
D Dichloromethane	M Nitric acid 65%	
E Carbon Disulfide	N Acetic acid 99%	
F Toluene	O Ammonia 25%	
G Diethylamine	P Hydrogen peroxide 30%	
H Tetrahydrofurane	S Hydrofluoric acid 40%	
I Ethyl acetate	T Formaldehyde 37%	

RADIOACTIVE CONTAMINATION EN 421



ELECTROSTATIC DISCHARGE PROTECTION EN 16350



For more details: www.mapa-pro.com

MAPA[®]
PROFESSIONAL

SPECIFIC ADVANTAGES

- Exceptionally comfortable textile support (no seams on the working surfaces)
- Excellent flexibility of natural latex
- Good thermal insulation

MAIN FIELDS OF USE

Environment

- Forestry
- Handling barbed wire
- Public park maintenance
- Waste collection

Other industries

- Wood working
- Spreading fertilizer
- Quarrying
- Glass working

INSTRUCTIONS FOR USE

Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at the workplace may differ from the "CE"-type tests.
- It is not recommended for persons sensitized to natural latex, dithiocarbamates and thiazoles to use these gloves.
- Put the gloves on dry, clean hands.

Storage conditions

- Store the gloves in their original packaging protected from direct sunlight, far from heat sources or electric equipment.

Laundering conditions

- Caution : improper use of the gloves or a cleaning or laundering process which is not specifically recommended can alter their performance levels.

Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/12/18/2943
- **Issued by the notified body nr** : 0075 - C.T.C. - 4 rue Herman Frenkel - 69367 LYON Cedex 07 FRANCE