



Dry



Wet



Heat



Oily



Cold



Chemical



TG1240

A high performing 15gg Cut A glove with ¾ dipped MicroDex Ultra coating, providing excellent grip in wet, dry and oily conditions. Treated with our Life Extending Technology for extra longevity and enhanced resistance to oil, dirt and water.

Key Features

- High tenacity nylon liner – widely known for its tensile strength and cut resistance
- Palm dip MicroDex Ultra coating for further longevity and abrasion resistance
- Hot contact resistance up to 100°C
- LXT Treatment for water, oil and dirt resistance and reduced staining
- Dexterous, highly tactile, and breathable

Ideal for

- Assembly work which requires precision
- Automotive industry
- Light construction tasks
- General maintenance

Sizes:	6-11	Gauge:	15gg
Liner:	Nylon	Coating:	MicroDex Ultra
No/Bag:	10	No/Carton:	100



TG1240

Glove Specifications

Glove lengths

220mm-270mm

Glove Weight

15 gauge

Liner Type

Polymide Nylon

Glove colour

Pantone 1795c / R:223 G:59 B:48 / C:8 M:96 Y:100 K:1

Overlock Colours

SIZE	XS - 6	S - 7	M - 8	L - 9	XL - 10	2XL - 11
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK

Coating Specifications

Coating colour

Black

Dip type

Nitrile Microfoam

Dip Application

Palm Dipped

Glove Treatment

Patent pending LXT Treatment



Packaging Information

Qty/bag

10 pairs

Qty/carton

100 pairs

Carton Dimensions

290mm x 440mm x 280mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.