

Antistatic Gloves 23502-4 M-L

CAT II

These products are classed as Personal Protective Equipment by the European PPE Directive 89/686/EEC

Notified Body: Intertex, Centre Court, Meridian Business Park, Leicester, LE19 1WD United Kingdom. NB: 0362

CAREFULLY READ INSTRUCTIONS BEFORE USE

This product is designed to provide protection against: Mechanical Risks. No item of PPE can provide full protection - care must always be taken whilst carrying out the activity.

EN 420:2003+A1:2009 Protective Gloves - General Requirements

Fitting & Sizing: Only wear products of a suitable size. Products which are either too loose or too tight will restrict movement and will not provide the optimum level of protection.

Storage & Transport: Store the product in a well ventilated area away from extremes of temperature & strong odours.

Inspection Before & After Use: Discard and replace damage products before use. If in doubt consult manufacturer.

Cleaning: It is recommended that this product should not be washed or dry-cleaned.

EN 388:2003 Protective Gloves Against Mechanical Risks

| Test | Level Achieved | Maximum Level |
|----------------------|----------------|---------------|
| Abrasion Resistance | 0 | (4) |
| Blade Cut Resistance | 0 | (5) |
| Tear Resistance | 1 | (4) |
| Puncture Resistance | 1 | (4) |

Note: Performance levels apply to the palm area of the hand.

Warning: These gloves will not prevent crushing injuries, or injuries associated with vibration. They are not to be worn when there is a risk of entanglement by moving parts of machinery.

Gloves containing natural rubber latex might contain ingredients which are known to be a possible cause of allergies in sensitised persons. If any allergic reaction should occur then medical advice should be obtained immediately.





To find DOC documentation search for your desired product at- www.supertouch.com